# ProLite E2409HDS-1

iiyama's ProLite E2409HDS is yet another product to follow the true HD resolution of 1920 x 1080. The incredible 2msec Response Time and 20,000:1 Contrast Ratio panel ensures vibrant images and blur free Video. Triple Input support of Analogue, DVI and HDMI ensures compatibility with the latest installed graphics cards and embedded Notebook outputs!

| | |
|---|---|
| Panel | TN |
| Diagonal | 24" |
| Display area h x w | 293.2 x 521.3 mm; 11.54" x 20.51" |
| Response time | 2 ms |
| Contrast | 20 000 : 1 ACR |
| Contrast | 1000 : 1 typical |
| Brightness | 300 cd/m² typical |
| Viewing zone | horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 80°/80° |
| Display colour | 16.7 million |
| Pixel pitch h x v | 0.2715 x 0.2715 mm |
| Native resolution | Full HD 1080p, 1920 x 1080 (2.1 megapixel) |
| Horizontal sync | 24 - 80 KHz |
| Vertical sync | 55 - 75 Hz |
| Analog input connector | D-Sub |
| Digital input connector | DVI-D, HDMI |
| HDCP | yes |
| Output connector | headphone socket |
| Synchronization | Separate Sync |
| Plug & Play | VESA DDC2B™ |
| Speakers | 2 x 2 W (Stereo) |
| Included accessories | Power Cable, D-Sub Cable, DVI-D Cable, Audio cable, user manual, stand |
| Apple - Mac | All iiyama monitors are compatible with Apple-Macintosh computers. |
| Controls | Via OSD in 9 languages (EN, DE, FR, ES, IT, PT, Chinese, RU, JP) and 5 front controls (Power, Menu /Select Button, + /Volume Button (+), - / Eco Button (-), Auto) |
| User controls | luminance (contrast, brightness, ECO, picture mode, ACR), image setup (clock, phase, H. position, V. position, aspect), colour adjust (gamma, colour temperature), OSD setup (H. position, V. position, timeout, language), others (reset, signal select, HDMI audio, information), volume, auto adjust |
| Driver | Windows 95 / 98 / 2000 / ME / XP / Vista/ 7 |
| Ergonomics | TCO '03 |
| Safety | CE, TÜV-GS |
| Power supply | AC 100 - 240 V, 50 / 60 Hz |
| Power Supply Unit | internal |
| Power usage | 43 W typical; max. 1 W in Power management mode |
| Power management | VESA DPMS |
| Anti-theft-device | Kensington-lock™ prepared |
| VESA mounting | 100 mm |
| Tilt angle | 20° up; 5° down |
| Dimensions w x h x d | 561 x 398.5 x 201 mm |
| Weight | 5.3 kg |
| Aspect ratio | 16 : 9 |

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.